

General Information

1995

Chassis: EE3

CRT: A66EGW83X101

Remote Control:

290P054070

Door Flap - TV: 752C603030

Door Flap - Sat:

752C602090 (BD)

Door Flap - Sat:

752C6020000 (LD)

Door Flap - Sat:

752C602030 (BDS)

Door Catch - Fixed:

761C550010

Door Catch - Openable:

761C573010

Main Power Button:

754C600050


Matrix

Item	See Model
------	-----------

Safety Precautions	Mitsubishi CT-14MS1
Service Adjustments	Mitsubishi CT-21AV1B
EEPROM Initialisation	Mitsubishi CT-25AV1BD
Safety Parts	Mitsubishi CT-25AV1BD
Audio Power	
Amp Diagram	Mitsubishi CT-25AV1BD
Dolby Diagram	Mitsubishi CT-25AV1BD
Satellite Diagram	Mitsubishi CT-21AV1BS
Text Diagram	Mitsubishi CT-28AV1B


Specifications

Reception System: CCIR-I PAL
Reception Frequency: UHF 470MHz -862MHz
(all models)
VHF 47 - 170MHz (VB1),
170 - 448MHz (VB2)
(LD models only)
Mains Input: AC 230V 50Hz
Power Consumption: 112W (28AV1BD LD)
130W (28AV1BDS)
Aerial Input: 75 ohm
Intermediate Frequency: Video: 39.5MHz
Sound: 33.5MHz
Audio Output: 2 x 12W (L/R) - 15W (Woofer)
- 12W (Centre) - 2 x 6W (Rear)
(28AV1 models)
Speakers: 2 x 10cm + 4cm (L/R)
- 10cm (Woofer) - 12 x 8cm (Centre)
- 2 x 10cm (Rear)
(28AV1 models)

Continued at **1**

Main Diagram Cont'd.

1

Continued at **2**

Main Diagram Cont'd.

