


TOSHIBA

COLOUR TELEVISION


207X3M

See also FILE NO. 020-637
 for model 219X3M




SPECIFICATIONS


POWER INPUT RATING	70 watts (nominal), AC90 ~ 270 volts, 50/60Hz
AERIAL INPUT IMPEDANCE	75 ohm unbalanced type VHF and UHF
RECEIVING CHANNELS	PAL B/G, SECAM B/G system Any of VHF channels channels 2 to 12 Any of UHF channels channels 21 to 69 PAL D/K, SECAM D/K system Any of VHF channels channels 1 to 12 Any of UHF channels channels 21 to 69 PAL I system Any of UHF channels channels 21 to 69 NTSC Standard (US M/JAPAN M) system Any of VHF channels channels 2 to 13/1 to 12 Any of UHF channels channels 14 to 78/13 to 62 NTSC 3.58/5.5 System } VTR Play Back NTSC 4.43/5.5 System } PAL 50/60Hz System } VIDEO DISK Play Back SECAM 50/60Hz System } NTSC 50/60Hz System }
INTERMEDIATE FREQUENCIES	Picture I-F carrier frequency 38.9MHz Sound I-F carrier frequency 33.4MHz
CHASSIS CONSTRUCTION	IC Solid State, Horizontal Chassis
PICTURE TUBE	A48JAN33X(W) (48.0 cm measured on diagonal of viewable picture area) 90° Deflection
SOUND OUTPUT	2.3 watts (at 10% harmonic distortion), Max. 3 watts
SPEAKER	Oval: 6 cm x 9 cm
CABINET	Plastic Portable Type
DIMENSION	Height 46.5 cm Width 50.0 cm Depth 47.5 cm
WEIGHT (NET)	19.0 kg



U902 CRT DRIVE BOARD PW3943-2




SCHEMATIC DIAGRAM < MODEL 207X3M >
U501 SECAM CHROMA UNIT PW 3888




UA02 KEY BOARD PW3945-1


UA02 CONTROL BOARD PW3945-2




PW3943-1 MAIN BOARD



PW3943-2 CRT DRIVE BOARD



PW3943-3 SYS. IND. BOARD



PW3944 RMT/AUTO BOARD

