


TOSHIBA

COLOUR TELEVISION

218R8E:198R8E



SPECIFICATIONS


Power Input Rating :	71 watts (normal), AC 175 ~ 270 volts, 50/60Hz		
Aerial Input Impedance :	75 ohm unbalanced type for VHF and UHF		
Receiving Channels :	Any of VHF channels	channels 2 to 12	
	Any of UHF channels	channels 21 to 69	
Intermediate Frequencies :	Picture I-F carrier frequency	38.9MHz	
	Sound I-F carrier frequency	33.4MHz	
	Colour sub-carrier frequency	34.47MHz	
Picture Tube :	(218R8E) A51JAR97X03(VMW) (51 cm measured on diagonal of viewable picture area)		
	(198R8E) A46JAR97X01(PMW) (46 cm measured on diagonal of viewable picture area)		
Sound Output :	5 watts (at 10% harmonic distortion)		
Speaker :	Oval : 6 cm x 7 cm		
Cabinet :	Plastic portable type		
Dimension :		(218R8E)	(198R8E)
	Height	48.5 cm	45.0 cm
	Width	50.7 cm	46.5 cm
	Depth	48.2 cm	45.2 cm
Weight (Net) :	22 kg (218R8E), 19 kg (198R8E)		

Specifications are subject to change without notice.


DIFFERENCES BETWEEN 218R8E AND 198R8E

	218R8E	198R8E
MAIN BOARD NO.	PW6890-1	PW9000-1
CRT DRIVE BOARD NO.	PW6890-2	PW9000-2
C442	0.39(200V)	0.33(200V)
R327	2.2K(1/2W)	1.2K(1/2W)
L462	TDY621EA	TDY6195A
L901	TSB2283	TSB2284
V301	A51JAR97X03(VMW)	A46JAR97X01(PMW)

9	IF
10	GND
11	+8
12	AFT
13	AGC
14	VIDEO OUT



AERIAL INPUT



MAIN BOARD PW6890-1 (218R8E)
PW9000-1 (198R8E)
BOTTOM (FOIL) SIDE

